

Three in One 4K UHD Speaker Microphone Array AI Smart Tracking



**4k All-in-one USB Video Bar**  
**MODEL: LVC05SB**

LUXVIEW

AV SMART SYSTEM



## MAIN FEATURES

### 4K UHD

Use a high-quality 1/2.5 inches UHD CMOS sensor with 8.51 million pixels. Support max 4K30fps image output and multiple lower resolutions like 1080p/720p.

### Integrated Design

The three-in-one design incorporating the 4K UHD camera, the beamforming microphone and the full frequency speaker helps reduce wiring and makes available easy video communication.

### Wide FOV

121 ° wide FOV (110 ° horizontal FOV), and 5x zoom; optical lenses tailored for video conferences; built-in electric tripod head horizontal and pitch  $\pm 15^\circ$  ); easier for participants to be videoed.

### Beamforming Microphone

Built-in beamforming (BF) microphone, pickup distance is 6m; the lowdistortion transverse beamforming algorithm guides the microphone to speaker for better sound effect and make communication more clear, full and true.

### Full-frequency Speaker

The acoustically designed high-fidelity speaker minimizes interference and offers extraordinary sound effects.

### Easy to Deploy

Flexible installation such as desktop, wall-mount, and TV/display mount are available for quick install and deploy in a crowded conference room.

### PnP

Connection to PCs or commercial large screens is realized through PnP USB ports; the out-of-the-box mechanism helps reduce wiring and offers easy-to-handle video communication, thereby lowering the user thresholds.

### Audio 3A Algorithm

The built-in audio 3A algorithm (AEC/AGC/ANS) and full-duplex mode meet the communication requirements of various rooms; people who sit at the conference table, sit or stand next to you can talk comfortably and clearly.

### Speaker Phone

Mobile phones and other devices can connect to this device via Bluetooth and use it as Bluetooth microphone and loudspeaker, and to connect phone calls to audio and video conferences.

### Intelligent Analysis

Built-in intelligent analysis algorithm, voice recognition, participants automatic frame selection, speaker automatic tracking and switching speaker screen to ensure that the speaker is always clear in the screen.

### Bluetooth 5.0

Using Bluetooth 5.0 technology, compared with the previous generation technology, the transmission speed is increased by 2 times, and the transmission distance is increased by 4 times. Better transmit the high-quality audio between mobile phone and tablet devices to achieve the wireless Bluetooth streaming.

### Rich Interfaces

HDMI 1.4b and USB3.0 supported; simultaneous output of UHD audios and videos is available

## Camera Spec

Signal System	4KP30, 1080P30, 720P30 etc.
Sensor	1/2.5 inches, CMOS, Effective Pixels: 8.51 Megapixels
Optical Lens	121° (DFOV), 110° (HFOV), 75° (VFOV), 5x zoom Horizontal/pitch ±15°
PTZ	Mechanical PTZ (MPT) + e-PTZ (EPTZ)
Digital Noise Reduction	2D & 3D Digital Noise Reduction
Backlight Compensation	Support
SNR	≥ 55dB

## Audio Features

Full-frequency Speaker	96 dB SPL at 0.5 m
Microphone Array	Beamforming microphone with 6m pickup distance
Expansion MIC	Support (Optional)

## I/O

HD Output	1 x HDMI, Version 1.4b
Network Interface	1 × RJ45:10M/100M adaptive Ethernet (Optional)
USB Interface	1 × USB3.0, Type-C ; 1 × USB2.0, Type-A
Bluetooth	5.0

## USB Spec

Type of Connection	USB 3.0, downward compatible with USB 2.0
Color System /Compression	YUY2 / MJPEG
USB Audio	32K sampling rate, UAC 1.0 support
USB Video Communication Protocol	UVC 1.1
UAC	Support
UVC PTZ Control	Support (ePTZ)

## Others

Installation Method	Support desktop placement, wallmounting and TVmounting etc.
Supplied Cables	USB Cable
Safety Protection	Anti-theft lock

## Generic Spec

Power Supply Operating	DC 12V, 2A(Max.)
Temperature Storage	0° C ~ 40° C
Temperature	-40° C ~ 60° C
Dimension	601mm (W) × 141mm (D) × 115mm (H) (with bracket)
Net Weight	2.5kg



## Disclaimer

Affected by product configuration and manufacturing process, the actual body size/body weight may be different, please refer to the actual product. The product images in this specification are for illustrative purposes only. The actual product effect (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product.

In order to provide accurate specifications as far as possible, the text description and picture effects of this specification may be adjusted and revised in real time, so as to match the actual product performance, specifications and other information.

© 2024 LUXVIEW The logo and other LUXVIEW marks are owned by LUXVIEW and may be registered. All other trademarks are the properties of their respective owners. LUXVIEW assumes no responsibility for any errors that may appear in this publication. Product, pricing and feature information contained herein is subject to change without notice