



1080P



AI Smart Tracking



ISP



Low delay



Multiple Interface



LUXVIEW

AV SMART SYSTEM



Full HD Intelligent Professional PTZ Camera MODEL: LVC12

MAIN FEATURES

- **1080P Full HD**

Equipped with 1/2.8", 2.07 million effective pixels high quality HD CMOS sensor, can reach maximum 920 x 1080 high resolution and achieve quality image.

- **New Generation of ISP Image Processing Algorithm**

The new generation of ISP image processing algorithm provides more complete white balance and automatic exposure functions, which significantly improves the image output performance of the camera, and the imaging effect is also better. Widely used in education recording and broadcasting, distance education, video conferencing, live broadcasting, broadcasting and other industries.

- **Upgraded AI Technology**

Using upgraded AI technology, through face recognition, it can accurately determine the location of people, realize automatic tracking and automatic frame selection.

- **1080P60 NDI®|HB (Optional)**

It supports 1080P60 NDI®|HB technology, which brings us ultra-low latency high-quality audio and video signal transmission, which can achieve unparalleled ultra-high-resolution image quality and lossless effects that are closer to vision.

- **AAC Audio Encoding**

Support AAC audio encoding, better sound quality and smaller bandwidth.

- **Leading Auto Focus Technology**

Using advanced focusing algorithm, the lens can focus quickly, accurately and stably.

- **72.5° Wide-angle Lens + 12x Optical Zoom**

Use 72.5° wide-angle high quality lens, support 12x optical zoom.

- **Exclusive Audio Processing Algorithm**

The exclusive audio processing algorithm can eliminate reverberation, effectively reduce environmental noise, and support EQ adjustment to optimize sound effects; the device supports dual mic pickup, and can also be connected to external microphones, wireless bees, etc., to meet the pickup needs of most scenarios.

- **Low Illumination**

The application of 2D and 3D noise reduction algorithm greatly reduces image noise. Even under the condition of ultra-low illumination, it still keep the picture clean and clear, and the SNR of image is as high as 55dB.

- **Multiple Interfaces**

Support HDMI output, Network, USB can output at the same time.

- **Remote Control**

Through the RS485 serial ports and USB, the camera can be controlled remotely.

Camera	
Sensor	1/2.8-inch, CMOS
Effective Pixel	2.07M
Scanning Mode	Progressive
Lens	12x, f=3.5mm ~ 42.3mm, F1.8 ~ F2.8
Digital Zoom	16x
Minimum Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, VAR, Manual, One Push, Indoor, Outdoor
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
SNR	≥55dB
Horizontal FOV	72.5° ~ 6.9°
Vertical FOV	44.8° ~ 3.9°
Pan Angle	±170°
Tilt Angle	-30° ~ +90°
Pan Speed	1.7° ~ 100°/s
Tilt Speed	1.7° ~ 69.9°/s
Image Flip	Support
Image Freeze	Support
Preset Position	255
Preset Accuracy	0.1°
USB Features	
Operate System	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
Color System / Compression	MJPEG/YUY2/H.264
Video Format	1080P60, 1080P59.94, 1080P50, 1080I60, 1080I59.94, 1080I50, 1080P30, 1080P29.97, 1080P25, 720P60, 720P59.94, 720P50
USB Audio	Support
USB Video Protocol	UVC 1.1/UVC 1.5
UVC PTZ Control	Support
Interfaces	
USB Interface	1 x USB 3.0: Type C
LINE IN Interface	1 x LINE IN: 3.5mm Audio Interface

Communication Interface	1 x RS485
Protocol:	VISCA/Pelco-D/Pelco-P
Network Interface	1 x RS485: 2pin phoenix port, Max Distance:1200m, 1 x LAN: 10M/100M Adaptive Ethernet Port
HDMI Interface	1 x HDMI: Version 1.3
Power Jack	JEITA type (DC IN 12V)
General Specifications	
Input Voltage	DC 12V
Input Current	Max. 1.2A
Operating Temperature	-10°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Power Consumption	Max. 12W
Dimension	144mm x 144mm x 167.9mm
Net Weight	About 1.28Kg
Network Features	
Video Compression	H.264/H.265
Video Stream	First Stream, Second Stream
MainStream	1920x1080,1280x720,1024x576,960x540,640x480,640x360
Sub Stream	1280x720,1024x576,720x480,720x408,640x360,320x240, 320x180
Video Bit Rate	32Kbps ~ 20480Kbps
Bit Rate Control	CBR, VBR
Frame Rate	1fps ~ 60fps
Audio Compression	AAC
Audio Bit Rate	96Kbps, 128Kbps, 256Kbps
Protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.



Disclaimer

Affected by product configuration and manufacturing process, the actual body size/body weight may be different, please refer to the actual product. The product images in this specification are for illustrative purposes only. The actual product effect (including but not limited to appearance, color, size) may be slightly different, please refer to the actual product.

In order to provide accurate specifications as far as possible, the text description and picture effects of this specification may be adjusted and revised in real time, so as to match the actual product performance, specifications and other information.

© 2024 LUXVIEW The logo and other LUXVIEW marks are owned by LUXVIEW and may be registered. All other trademarks are the properties of their respective owners. LUXVIEW assumes no responsibility for any errors that may appear in this publication. Product, pricing and feature information contained herein is subject to change without notice